



1.3"+10"  
SUBWOOFER



SPEAKON  
INPUT/OUTPUT



250W/500W  
RMS/PEAK



15kg  
GROSS WEIGHT

FEATURES

- ✓ M-210 is monitor speaker designed for stage. Enclosure angle with ground is 55° to 35° optional, depends on distance stage needs, it provide as monitoring for Vocal/Musician in Stage.
- ✓ M-210 is 2-Way Full-Range System Speaker Series, features low-distortion high-efficiency characteristics and comprises of and 10"LF & 1,3"HF Driver Unit, equips with 50° ~ 100° Horizontal x 50° Vertical constant direction horn to reduce sound interfere and ensure clear sound.

APPLICATION

Live Sound Monitor at Show / Stage, for Band, Conference Hall, Multi-Function Hall, or could be use for Side Monitor, etc.

DETAIL PRODUCT



Power	250W RMS   500W Peak
Impedance	8Ω
Drive Unit	1,3" Tweeter   10" Subwoofer
Frequency Response	58Hz -18KHz(±3dB)
Sensitivity	96dB
Max.Continuous SPL	118dB
Max.Peak SPL	124dB
Dispersion	50 ~ 100° Hor x 50° Ver
Input/Output	2 x NL4R Speakon
Dimension (LxWxH)	280 x 320 x 515mm
Gross Weight	15kg
Rec.Amplifier	500W/8Ω ~ 600W/8Ω (XS.6.2)